

Madagascar Multimode Fiber Attenuator Models



Overview

These attenuators are suitable for use in single mode 9/125, multimode 50/125, and multimode 62. Our male-to-female buildout optical attenuation (Pads) are available across all fiber modes, featuring LC, LC/APC, SC, SC/APC, FC, FC/APC, and ST. The N7768C is a four-channel power-monitored optical attenuator for multimode fiber applications. Its bulk-optic filter and collimated beam path is designed to assure homogeneous attenuation of all input modes. It maintains the beam profile of signals that comply with the encircled flux conditions. Fibertronics, Inc. provides an extensive selection of fiber optic attenuators tailored to meet diverse needs. We offer SM and PM electronic VOAs that provide control of the output power with FC/PC or FC/APC connectors. No special mounting is required. Plug the SEL-9220 EIA-485 adapter directly onto an SEL-300 series EIA-485 port.

Madagascar Multimode Fiber Attenuator Models



Our SM fixed optical attenuators are fiber connectors that can be attached to an FC/PC or FC/APC SM fiber patch cable. We also offer variable optical attenuators for MM fibers with FC/PC or SMA ...



These attenuators are suitable for use in single mode 9/125, multimode 50/125, and multimode 62.5/125 applications. Our male-to-female buildout optical attenuation (Pads) are available across all fiber ...



Shop DigiKey's large in-stock selection of Fiber Optic Attenuators. View inventory, pricing and order now for same day shipping!



FS fixed and variable fiber optic attenuators with leading attenuating fibers guarantee consistent and stable fiber attenuation (0~60dB) in WDM transmission.



The N7768C is a four-channel power-monitored optical attenuator for multimode fiber applications. Its bulk-optic filter and collimated beam path is designed to assure homogeneous attenuation of all input ...



The fiber-optic attenuator kit (SEL part number 91560) adds a spacer on the transmit side of the ST connectors. This pushes the fiber away from the transmitted light and reduces the transmit power by ...



Length:40.5mm
Small-end inner diameter:2.0mm
Large-end inner diameter:6.0mm
Outer diameter:7.5mm

Our multimode fiber optic filter/attenuator mount is capable of holding a variety of filters and a shutter-based attenuator; it is also designed for SMA patch cables.



Useful in all networks including WDM and EDFA system applications with high-power laser sources, these single-mode and multimode fiber attenuators are manufactured using doped fiber, provide ...



Based on the revolutionary OptoCeramic™ electro-optic technology, the MM-VOAs achieve very high speeds in a compact solid-state device.



Angnet's Fiber Optic Pigtails are manufactured with either multimode or single-mode fibre and terminated with a range of connectors including SC, SC/APC, LC, LC/APC, FC, FC/APC, ST and MTRJ.

Contact Us

For more information, pricing, or custom solutions, please contact us:

Website: <https://www.samastersbaseball.co.za>

Email: sales@samastersbaseball.co.za

Phone: +27 63 874 2095

Address: 15 Innovation Drive, Technopark, Stellenbosch, 7600, South Africa

This document is for informational purposes only. Specifications subject to change without notice.

