

XI22 distribution box dimensions



Overview

This publication contains the following new or updated information. This list includes substantive updates only and is not intended to reflect all changes.




XL22 distribution box dimensions



DC Micro Style Distribution Boxes Four-pin, One Signal per Port Cable Connector Distribution Box Eight-port DC Micro Distribution Box Specifications




The document provides details for designing the electrical distribution box and circuits for a residence. It includes specifications for the main circuit breaker such as size, type, and tripping capacity.



The XL22 family takes versatility to the next level with 4 low-profile housing sizes and field-adjustable switches for wattage, CCT, and beam angle. An integrated photocell with on/off switch provides built ...



FACTORY SETTINGS Wattage XL22-35: 35/30/25/20W (default 35W) XL22-60: 60/50/40/30W (default 60W) XL22-80: 80/70/60/50W (default 80W) XL22-150: 150/125/100/75W (default 150W)



Driver includes dimming control wiring for 0-10V dimming systems. Requires separate 0-10V DC dimming circuit. Dims down to 10%. 12.57% at 120V, 18.08% at 277V. 99.2% at 120V, 96.8% at ...



Description: ATS Extrusion Profiles. 8 Results. Part #: ATS-EXL22-300-R0. Datasheet: 2MbKb/1P. Manufacturer: Advanced Thermal Solutions, Inc..



Driver includes dimming control wiring for 0-10V dimming systems. Requires separate 0-10V DC dimming circuit. Dims down to 10%. 7.62% at 120V, 11.64% at 277V. 99.6% at 120V, 95.3% at 277V. ...



Driver includes dimming control wiring for 0-10V dimming systems. Requires separate 0-10V DC dimming circuit. Dims down to 10%. 11.31% at 120V, 19.24% at 277V. 99.4% at 120V, 95.6% at ...



Distribution Box Metal Distribution Box Features Continuously welded seams Foam-in-place seamless gasket 120-degree opening heavy-duty industrial hinges IP66 protection rating against dust and ...



The document provides essential notes regarding product specifications, connections, and dimensions for a specific product. It emphasizes that dimensions are actual product sizes without clearance data ...

Contact Us

For more information, pricing, or custom solutions, please contact us:

Website: <https://www.samastersbaseball.co.za>

Email: sales@samastersbaseball.co.za

Phone: +27 63 874 2095

Address: 15 Innovation Drive, Technopark, Stellenbosch, 7600, South Africa

This document is for informational purposes only. Specifications subject to change without notice.

